



Solenoid coil, BG230AS

018F6801

Product name: Solenoid coil, Type: BG230AS,
Supply voltage [V] AC: 220.0 - 230.0, Enclosure
rating IP: IP67, Coil connection: Connection box,
Actuator size: 13.5 mm

**Contact: 0982 67 24 67 -
online@congnhieplanh.com**

Product details

Gross weight	0.5 kg
Net weight	0.48 kg
EAN	5702428027304
Actuator size	13.5 mm
Ambient temperature range [°C] [Max]	80 °C
Ambient temperature range [°C] [Min]	-40 °C
Ambient temperature range [°F] [Max]	175 °F
Ambient temperature range [°F] [Min]	-40 °F
Approval	LLC CDC TYSK
Coil connection	Connection box
Coil design standard	VDE 0580
Coil fastening	Clip-on
Coil winding insulation class	Class H to IEC 85

Colour	Blue
Compliance	EN 60730-1
Duty rating	Continuous
Electrical connection	Terminal box
Electrical connection size	Pg 13.5
Electrical connector	Screwed cable entry
Enclosure rating IP	IP67
Enclosure rating Nema (~)	6
Frequency [Hz]	50 Hz
Further information	Terminal box
Identical product	018F8801
Packing format	Multi pack
Parts Program name	EV210B EV212B EV220B 15 - 50 EV220B 6 - 22 EV220B 65 - 100 EV222B EV224B EV250B
Power consumption 50Hz [VA]	28 VA
Power consumption [W] 50Hz	15 W
Product accessories	Solenoid coil accessories
Product group	Solenoid valves
Product name	Solenoid coil
Quantity per packing format	24 pc
Rel. Humidity [% RH] [Max]	100 %

Rel. Humidity [% RH] [Min]	0 %
Serviceable	No
Spare part number	018F6801
Supply voltage 50Hz Max [V]	230 V
Supply voltage 50Hz Min [V]	220 V
Supply voltage [V] a.c. [Max]	230 V
Supply voltage [V] a.c. [Min]	220 V
Supply voltage [V] AC [Max]	230 V
Supply voltage [V] AC [Min]	220 V
Type	BG230AS
Type designation	BG230AS