



Thermostatic expansion valve, TE 2 068Z3209

Inlet connection type: FLARE, Outlet connection type: FLARE

Contact: 0982 67 24 67 -
online@congnghieplanh.com

Product details

Gross weight	0.33 kg
Net weight	0.29 kg
EAN	5702422117261
Approval	EAC LLC CDC TYSK
Body material	Brass
Capillary tube length [in]	59 in
Capillary tube length [mm]	1500 mm
Category	Art. 4, par. 3
Connection material	Brass
Direction	Angleway
Equalization connection type	FLARE
Equalization size [in]	1/4 IN
Flow direction	Bi-flow with orifice 01-05
Flow direction indicator	Embossed 1-way arrow

Fluid Group	II
Identical product	068Z3238
Inlet connection type	FLARE
Inlet size [in]	3/8 IN
Max. Working Pressure [bar]	34 bar
Max. Working Pressure [psig]	500 psig
Outlet connection type	FLARE
Outlet size [in]	1/2 IN
Packing format	Multi pack
Parts included	Bulb strap
Parts Program name	T2/TE2
Pressure equalization	Externally equalized
Product accessories	TXV accessories
Product family name	T2
Product group	Expansion valves
Product name	Thermostatic expansion valve
Quantity per packing format	20 pc
Rated cap. cond. Range N [IMP]	OS=10.8 °F tcond=100 °F tevap=40 °F tliq=98 °F
Rated cap. cond. Range N [SI]	OS=6K tcond=38 °C tevap=4.4 °C tliq=37 °C
Refrigerants	R22/R407C
Serviceable	TXV spare parts

Static Superheat (SS) [°C]	4 °C
Static Superheat (SS) [°F]	7.2 °F
Superheat setting	Adjustable
Temperature range [°C] [Max]	10 °C
Temperature range [°C] [Min]	-40 °C
Temperature range [°F] [Max]	50 °F
Temperature range [°F] [Min]	-40 °F
Type	TE 2
UL approved refrigerants	R22 R407C